

Department of Environmental Quality

Kimberly D. Shelley Executive Director

DIVISION OF AIR QUALITY Bryce C. Bird Director

DAQE-AN122880003-24

January 8, 2025

Shawn Bishop Concrete Recycling Incorporated 555 South Iron Rose Place Salt Lake City, UT 84104 shawn@impactdemolition.net

Dear Mr. Bishop:

Re: Approval Order: Administrative Amendment to Approval Order DAQE-AN2288003-04 for a

10-year Review and Permit Updates Project Number: N122880003

The attached Approval Order (AO) is issued pursuant to the Division of Air Quality conducting a 10-year administrative review of this source and its respective AO. Concrete Recycling Incorporated must comply with the requirements of this AO, all applicable state requirements (R307), and Federal Standards.

The project engineer for this action is **John Persons**, who can be contacted at (385) 306-6503 or jpersons@utah.gov. Future correspondence on this AO should include the engineer's name as well as the DAQE number shown on the upper right-hand corner of this letter.

Sincerely,

Bryce C. Bird

In CITI

Director

BCB:JP:jg

STATE OF UTAH Department of Environmental Quality Division of Air Quality

APPROVAL ORDER DAQE-AN122880003-24 Administrative Amendment to Approval Order DAQE-AN2288003-04 for a 10-Year Review and Permit Updates

Prepared By John Persons, Engineer (385) 306-6503 jpersons@utah.gov

Issued to Construction Recycling Incorporated - Construction Debris Recycling

Issued On January 8, 2025

Issued By

Sucite

Bryce C. Bird
Director
Division of Air Quality

TABLE OF CONTENTS

TITLE/SIGNATURE PAGE	1
GENERAL INFORMATION	3
CONTACT/LOCATION INFORMATION	3
SOURCE INFORMATION	3
General Description	3
NSR Classification	3
Source Classification	3
Applicable Federal Standards	3
Project Description	4
SUMMARY OF EMISSIONS	4
SECTION I: GENERAL PROVISIONS	4
SECTION II: PERMITTED EQUIPMENT	5
SECTION II: SPECIAL PROVISIONS	6
PERMIT HISTORY	8
ACRONYMS	9

GENERAL INFORMATION

CONTACT/LOCATION INFORMATION

Owner Name

Concrete Recycling Incorporated

Mailing Address

555 South Iron Rose Place Salt Lake City, UT 84104

Source Contact

Name: Shawn Bishop Phone: (801) 973-0066

Email: shawn@impactdemolition.net

Source Name

Construction Recycling Incorporated - Construction Debris Recycling

Physical Address

620 South Delong Street Salt Lake City, UT 84104

UTM Coordinates

419,497 m Easting 4,512,062 m Northing Datum NAD83 UTM Zone 12

SIC code 5093 (Scrap & Waste Materials)

SOURCE INFORMATION

General Description

Construction Recycling Incorporated operates a permanent aggregate operation that processes construction debris into road-base gravel and fill material in Salt Lake County, Utah. The facility includes feeders, crushers, screens, stackers, and associated conveying equipment. The facility produces up to 400,000 tons of processed material per year.

NSR Classification

10-Year Review

Source Classification

Located in Northern Wasatch Front O3 NAA, Salt Lake City UT PM_{2.5} NAA, Salt Lake County SO₂

NAA

Salt Lake County Airs Source Size: B

Applicable Federal Standards

NSPS (Part 60), A: General Provisions

NSPS (Part 60), OOO: Standards of Performance for Nonmetallic Mineral Processing Plants

MACT (Part 63), A: General Provisions

MACT (Part 63), ZZZZ: National Emissions Standards for Hazardous Air Pollutants for

Stationary Reciprocating Internal Combustion Engines

Project Description

This project is a 10-year review of Approval Order DAQE-AN2288003-04 dated April 20, 2004.

SUMMARY OF EMISSIONS

The emissions listed below are an estimate of the total potential emissions from the source. Some rounding of emissions is possible.

Criteria Pollutant	Change (TPY)	Total (TPY)
Carbon Monoxide	0	2.03
Nitrogen Oxides	0	17.20
Particulate Matter - PM ₁₀	0	4.47
Particulate Matter - PM _{2.5}	0	4.47
Sulfur Dioxide	0	3.28
Volatile Organic Compounds	0	0.93

SECTION I: GENERAL PROVISIONS

I.1	All definitions, terms, abbreviations, and references used in this AO conform to those used in the UAC R307 and 40 CFR. Unless noted otherwise, references cited in these AO conditions refer to those rules. [R307-101]
I.2	The limits set forth in this AO shall not be exceeded without prior approval. [R307-401]
I.3	Modifications to the equipment or processes approved by this AO that could affect the emissions covered by this AO must be reviewed and approved. [R307-401-1]
I.4	All records referenced in this AO or in other applicable rules, which are required to be kept by the owner/operator, shall be made available to the Director or Director's representative upon request, and the records shall include the two-year period prior to the date of the request. Unless otherwise specified in this AO or in other applicable state and federal rules, records shall be kept for a minimum of two (2) years. [R307-401-8]
I.5	At all times, including periods of startup, shutdown, and malfunction, owners and operators shall, to the extent practicable, maintain and operate any equipment approved under this AO, including associated air pollution control equipment, in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Director which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source. All maintenance performed on equipment authorized by this AO shall be recorded. [R307-401-4]
I.6	The owner/operator shall comply with UAC R307-107. General Requirements: Breakdowns. [R307-107]
I.7	The owner/operator shall comply with UAC R307-150 Series. Emission Inventories. [R307-150]

SECTION II: PERMITTED EQUIPMENT

II.A THE APPROVED EQUIPMENT

II.A.1	Site Wide Requirements
II.A.2	One (1) Jaw Crusher Rated: 250 tph Manufacturer: Universal Model: 1208 S/N: 115.257 Manufactured: 1999
II.A.3	One (1) Feeder Rated: 250 tph Manufacturer: Universal Model: 44x20 S/N: 65A-011 Manufactured: 1999
II.A.4	One (1) Feeder Rated: 250 tph Manufacturer: Universal Model: 44x20 S/N: 806x640 Manufactured: 1999
II.A.5	One (1) Impact Crusher Rated: 400 tph Manufacturer: Universal Model: 130/150 S/N: 619/315 Manufactured: 1999
II.A.6	One (1) Triple Screen Rated: 250 tph Manufacturer: Allis Model: 1208 S/N: 26A298 Manufactured: 1999
II.A.7	Associated Equipment Loaders, excavators, water and haul trucks, conveyors, magnet towers, and stackers

SECTION II: SPECIAL PROVISIONS

II.B REQUIREMENTS AND LIMITATIONS

II.B.1	Site-wide Limitations
II.B.1.a	The owner/operator shall ensure that visible emissions from the following emission points do not exceed the specified values:
	A. All crushers - 12% opacity
	B. All screens - 7% opacity
	C. All conveyor transfer points - 7% opacity
	D. All diesel engines - 20% opacity
	E. Conveyor drop points - 10% opacity
	F. All other points - 20% opacity.
	[R307-401-8]
II.B.1.a.1	Opacity observations of emissions from stationary sources shall be conducted according to 40 CFR 60.11(b) and 40 CFR 60, Appendix A, Method 9. [R307-401-8]
II.B.1.b	The owner/operator shall not produce more than 400,000 tons of processed materials per rolling 12-month period. [R307-401-8]
II.B.1.b.1	The owner/operator shall:
	A. Determine production by belt scale records or scale house records
	B. Record production daily
	C. Use the production data to calculate a new rolling 12-month total by the 20th day of each month using data from the previous 12 months
	D. Keep these records for all periods the plant is in operation.
	[R307-401-8]
II.B.1.c	The owner/operator shall not operate the facility more than the following hours:
	A. 14 hours per day
	B. 3000 hours per rolling 12-month period.
	[R307-401-8]

II.B.1.c.1	The owner/operator shall:
	A. Determine hours of operation by hour meters or an hours of operations log
	B. Records hours of operation daily
	C. Use the hours of operation to calculate a new rolling 12-month total by the 20th day of each month using data from the previous 12 months
	D. Keep hours of operation records for all periods the facility is in operation.
	[R307-401-8]
II.B.2	Fugitive Dust Requirements
II.B.2.a	The owner/operator shall abide by a fugitive dust control plan acceptable to the Director for control of all dust sources associated with the DeLong Street aggregate facility, and comply with the most current plan approved by the Director. [R307-401-8]
II.B.2.b	The owner/operator shall abide by all applicable requirements of the Utah Administrative Code (UAC) Section R307-309. [R307-309]
II.B.2.c	The owner/operator shall ensure that the haul road does not exceed 0.5 miles in length. [R307-401-8]
II.B.2.c.1	The owner/operator shall:
	A. Record the length of all haul roads using satellite imagery or measurement equipment, or other methods acceptable to the Director
	B. Keep a record of the total haul road length on site at all times the facility is in operation.
	[R307-401-8]
II.B.2.d	The owner/operator shall ensure that visible fugitive dust emissions from haul-road traffic and mobile equipment in operational areas do not exceed 20% opacity. [R307-401-8]
II.B.2.d.1	Opacity observations of fugitive dust from intermittent sources shall be conducted according to 40 CFR 60, Appendix A, Method 9; however, the requirement for observations to be made at 15-second intervals over a six-minute period shall not apply. The number of observations and the time period shall be determined by the length of the intermittent source. For fugitive dust generated by mobile sources, visible emissions shall be measured at the densest point of the plume but at a point not less than one-half vehicle length behind the vehicle and not less than one-half the height of the vehicle. [R307-401-8]
II.B.2.e	The owner/operator shall install water sprayers or chemical dust suppression sprayers at the following points to control fugitive emissions:
	A. All crushers
	B. All screens
	C. All conveyor transfer points.
	[R307-401-8]

II.B.2.e.1	The owner/operator shall ensure that the sprays operate whenever dry conditions warrant or as determined necessary by the Director. [R307-401-8]
II.B.2.f	The owner/operator shall ensure that the storage piles are watered to minimize the generation of fugitive dust, as dry conditions warrant or as determined necessary by the Director. Records of water and/or chemical treatment shall be kept for all periods when the plant is in operation. Records of water and/or chemical treatment shall be made available to the Director or Director's representative upon request, and the records shall include the two-year period prior to the date of the request. [R307-401-8]
II.B.2.g	The owner/operator shall perform monthly periodic inspections to check that water is flowing to discharge spray nozzles associated with each crusher, screen, and conveyor. If the owner/operator finds that water is not flowing properly during an inspection of the water spray nozzles, the owner/operator shall initiate corrective action within 24 hours and complete corrective action as expediently as practical. [40 CFR 60 Subpart OOO, R307-401-8]
II.B.2.g.1	Records of the water sprays inspections shall be kept and maintained in a logbook for all periods when the plant is in operation. The records shall include the following items: A. Date the inspections were made B. Any corrective actions taken C. Control mechanism used if sprays are not operating.
	[40 CFR 60 Subpart OOO, R307-401-8]

PERMIT HISTORY

This Approval Order shall supersede (if a modification) or will be based on the following documents:

AO DAQE-AN2288003-04 dated April 20, 2004 NOI dated June 5, 2024 Replaces

Is Derived From

ACRONYMS

The following lists commonly used acronyms and associated translations as they apply to this document:

40 CFR Title 40 of the Code of Federal Regulations

AO Approval Order

BACT Best Available Control Technology

CAA Clean Air Act

CAAA Clean Air Act Amendments

CDS Classification Data System (used by Environmental Protection Agency to classify

sources by size/type)

CEM Continuous emissions monitor

CEMS Continuous emissions monitoring system

CFR Code of Federal Regulations CMS Continuous monitoring system

CO Carbon monoxide CO₂ Carbon Dioxide

CO₂e Carbon Dioxide Equivalent - Title 40 of the Code of Federal Regulations Part 98,

Subpart A, Table A-1

COM Continuous opacity monitor DAQ/UDAQ Division of Air Quality

DAQE This is a document tracking code for internal Division of Air Quality use

EPA Environmental Protection Agency

FDCP Fugitive dust control plan

GHG Greenhouse Gas(es) - Title 40 of the Code of Federal Regulations 52.21 (b)(49)(i)
GWP Global Warming Potential - Title 40 of the Code of Federal Regulations Part 86.1818-

12(a)

HAP or HAPs Hazardous air pollutant(s)

ITA Intent to Approve LB/YR Pounds per year

MACT Maximum Achievable Control Technology

MMBTU Million British Thermal Units

NAA Nonattainment Area

NAAOS National Ambient Air Quality Standards

NESHAP National Emission Standards for Hazardous Air Pollutants

NOI Notice of Intent NO_x Oxides of nitrogen

NSPS New Source Performance Standard

NSR New Source Review

 PM_{10} Particulate matter less than 10 microns in size $PM_{2.5}$ Particulate matter less than 2.5 microns in size

PSD Prevention of Significant Deterioration

PTE Potential to Emit R307 Rules Series 307

R307-401 Rules Series 307 - Section 401

SO₂ Sulfur dioxide

Title IV Title IV of the Clean Air Act
Title V Title V of the Clean Air Act

TPY Tons per year

UAC Utah Administrative Code VOC Volatile organic compounds